

Description:

The Elite enclosed commercial range of festoon lighting comes in either 22M or 50M lengths with sealed for life ultrasonically welded light modules providing exceptionally water and dust protection. The 50M string comes with 20 modules delivering 560 lumens per module, a total of 11200 lumens with a wide light distribution of 120°.

Product Code: LEDKITENC50

Specification:

- 11200lm output
- Total power 160W, compared with 1200W using • conventional GLS variants.
- Compact and robust design
- CRI >80 and colour temperature of 6400K
- Fully CE compliant and manufactured to meet IP44.

Differentiator:

- Low heat, no hot surfaces or additional guarding requirements.
- Low profile none-intrusive design, essential for limited access installations.
- Moulded fixing bosses to ensure quick and secure • installation.
- All components are manufactured from robust materials to ensure the product performs in the harshest environments.

Technical:

- Voltage 110V 50/60Hz
- Plug 110V 16A IEC60309
- Weight 4.5kg
- Dims 335 x 260 x 275mm (LxDxH)
- Power 160W
- Lumens 11200lm
- Light distribution 120°



www.hscgroupuk.co.uk

The Hire Supply Company (UK) Limited

SALES: Telephone: 0845 3090707 Email: sales@hscgroupuk.co.uk





SMD LED





11200 LM







Rough Service



10°to +40°C

110Vac

